

The Pensteel Range of 210/216 Litre Steel drums

The Ecodrum Range of open top and tight head drums

Pensteel are now able to offer a selection of mild steel 210/216 litre capacity corrugated tight-head and corrugated open head drums for the transportation of hazardous liquid and viscous goods of UN packaging categories I, II and III.

Tight Head Drum

Cold-rolled thin sheet DC01Am compliant with DIN 10130.

Varying material thicknesses available. Standard manufacturing thickness of material -1mm, other material weights available upon request.

Inner surface protection: plain steel or lacquer-lined, ready for filling.

Exterior: Standard colour Blue, as an optional extra other colours are available upon request, including multiple colours and screen-painting of your company legend is available upon request.

Exterior height	884 mm
Exterior diameter	585 mm
Hazardous goods certification (min.)	UN 1A1/X/250/

Two rolling or negative hoops, additional reinforced hoops available on request. Bottom and lid with triple safety seam.

Safety screw fittings G2 and G3/4 on opposite sides of top.

Additional filling hole NW230 available.



Corrugated open head drum



Welded shell, flattened welding seam at fold and border area. Bottom and lid with triple safety seam.

Two rolling or negative hoops, additional reinforced hoops available on request.

Completely removable lid, upon request with safety screw fitting G2 and G3/4, on opposite sides of lid.

Gasket ring of cellular rubber. Clamp-ring of galvanized hoop with lever lock.

Additional filling hole NW180 available.

Exterior height	871 mm
Exterior diameter	585 mm
Hazardous goods certification (min.)	UN 1A2/Y120/ UN 1A2/Y150/

Available loose loaded or palletized and shrink wrapped on a CP9 timber pallet, and usually available ex stock for standard colours

Pensteel Limited

Unit 21 Seax Court, Southfields Business Park, Basildon, Essex. SS15 6SL.
Tel: 01268 545127 Fax: 01268 545188 Email: sales@pensteel.co.uk