

## The Pensteel Range of IBC Accessories – Insulated Covers

### Thermal and Waterproof Insulated IBC Jackets



#### Material & Technical Specifications

**Outer Surfaces:**

C-L Polyethylene – a rugged cross laminated sheet, light in weight, tear and fire resistant, anti-toxic, impervious to bacteria and will withstand -35° to +75°C.

**Thermal Wadding:**

Ref: No. BTB280. This has a CLO (warmth) factor equal to 2.00 or the same as the standard BSI 0.407m2.K/W. (9 TOG Rating)

**Standard Fittings:**

Two flaps fitted with Velcro to close the inlet and outlet: one centred in the top and one in the centre of the bottom on the valve side.

**Optional Extras;**

**Thermal Bases:**

In BTB280 attached to the cover with Velcro for maintaining maximum temperature.

**Document Pouches:**

Any size fitted can be used for paperwork relating to the IBC contents or destination.

**Binding:**

All edges can be bound to enhance the cover's appearance.

**Sizes:**

To fit the full Schütz range of Light Duty IBCs and the Finncont Oy. range of Heavy Duty IBCs. Other sizes on request.

*Folds Compactly for Storage or Return Transit*

**Pensteel Limited**

Unit 1 Horndon Industrial Park, West Horndon, Brentwood, Essex CM13 3XL  
Tel: 01277 810211 Fax: 01277 811971 Email: sales@pensteel.co.uk