

Pensteel Range of Heavy Duty Stainless steel IBCs

The Finncont CF unframed compact IBC

For liquid foodstuffs and chemicals.

The guiding principle of this design is ease of use. Thanks to the containers low structure, the fittings on the top surface are easily accessible. The use of space has been maximised; you will save both in transport and storage costs. With the centre of gravity being extremely low, this makes the container much safer to handle.

UN Certification is available where required - even up to a density of 2.6 on certain models. The IBC is easy to clean both internally and externally. The Finncont COMPACT CF IBCs provide an economic and durable solution which is demonstrated by containers which are still in continuous use after 20 years.

Efficiency in use is first class because the need to maintain the fittings and body structures is minimal, whilst the necessary servicing is easy to carry out. Dimensions comply with international standards and are compatible with other products on the market.

Technology:

- The IBC base gradient is selected in relation to the product being transported, (10°, 30° or 45°)

Material of construction depends upon the application and the product being transported, this can be Aluminium, mild steel (painted), or stainless steel (Aisi 304 or Aisi 316).

Materials for the pallet base are usually stainless steel (Aisi 304) or hot dip galvanised mild steel.

Manhole alternatives:

- 6 swing bolts, DN 400 - UN approved.
- Clamp ring, DN 400 - UN approved.
- Quick fastener, DN 400.
- Clamp ring, DN 460 - UN approved.



Valves and fittings:

- A comprehensive range of valves and fittings are stocked to allow choice depending on product requirements and customer preference.

Seal materials:

- A wide range of seal materials are now available, e.g. EPDM, Nitrile, Viton, PTFE, etc. It is important for the client to consider their choice of seal material carefully before ordering. Assistance is available if required.

Handling:

- With forklift from any side.
- With pallet truck from any side.
- With crane from four corners.
- Up to four full containers can be stacked on a flat level surface - 3 on 1.

Capacity	Length	Width	Height	Nett Wt
500	1225	1025	840	120 kg
1000	1225	1025	1260	152kg
2000	1225	1025	2160	250kg

Pensteel Limited

Unit 21 Seax Court, Southfields Business Park, Basildon, Essex. SS15 6SL.
Tel: 01268 545127 Fax: 01268 545188 Email: sales@pensteel.co.uk